

Jc 4/922

A standard linear barcode is positioned vertically on the right side of the page. It is used for tracking and identification purposes.

	Subclass
Class	

ISSUE CLASSIFICATION

U.S. UTILITY Patent Application

O.I.P.E. <i>HP Ed 3</i> SCANNED <i>Am</i>	PATENT DATE
--	--------------------

APPLICATION NO. 09/884778	CONT/PRIOR	CLASS 2624	SUBCLASS 262	ART UNIT 2847	EXAMINER J. K.
------------------------------	------------	---------------	-----------------	------------------	-------------------

APPLICANTS

Richard Hall,
Hou Lin
Christopher Majka
Matthew Seward

Dinh

三

Method and apparatus to establish circuit layers

PTO-2040
12/99

ISSUING CLASSIFICATION

<input type="checkbox"/> TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig. 6	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
	(Assistant Examiner)	(Date)			
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____				ISSUE FEE	
	(Primary Examiner)	(Date)	Amount Due	Date Paid	
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed.				ISSUE BATCH NUMBER	
	(Legal Instruments Examiner)	(Date)			

WARNING:

WARNING: The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)